



光语
GLORY

CloudEngine 5855F-G Data Center Switch



■ Product Overview

The CloudEngine 5855F-G series is a new generation of high-density Gigabit Ethernet switches for data centers. The CloudEngine 5855F-G adopts advanced hardware design, supports 10GE/40GE uplink and high-density Gigabit downlink, supports a maximum of nine stacked switches, and allows flexible choice of air channel direction. The CloudEngine 5855F-G series switches are designed for high-density gigabit access in data centers, helping enterprises and carriers build a data center network platform for the cloud computing era. They can also be used for aggregation or access of campus networks.

■ Technical Specification

Items	CloudEngine 5855F-48T4S2Q-G
Base-T Interface	48
SFP+ Interface	4
QSFP+ Port	2
Switching Capacity	1.28Tbps/11.52Tbps
Packet Forwarding Rate	252Mpps
Air Duct Type	Standard front/rear or rear/front air duct
Chassis Dimensions (W × D × H)	442mm × 420mm × 43.6mm
Full Weight	7.5Kg
Environmental Requirements	Operating Temperature: 0°C to 40°C (0m to 1800m) Storage Temperature: -40°C to +70°C Relative Humidity: 5% to 95%RH, non-condense
Typical Power Consumption	102W



光语
GLORY

Ignite future, connect world



Guangdong Glory Technology Co., Ltd.

Email: service@glory-t.tech

Hotline: +86 400-800-6805

For more information, please visit www.glory-t.cn

*The descriptions and information displayed in the product promotional materials are for reference only. The actual delivered product shall prevail. The final interpretation right belongs to GLORY.